



Digital Migration Radio PD485

- Clear Audio
- Built-in Bluetooth and GPS option
- Analogue and Digital Auto Detect





Features

- ↔
ANALOGUE & DIGITAL AUTO DETECT
 Compatible with analogue conventional and digital conventional modes. Allows PD485 to simultaneously monitor analogue and digital modes and automatically respond in each mode. Extremely easy migration to digital from analogue.
- 📡
DTMF SIGNALING
- 🕒
REAL TIME CLOCK
 Ensures the real time is displayed on the menu and GPS/messaging.
- 🔒
PRIVACY (Optional)
 Basic end-to-end Encryption has your voice and data transmission secured.
- 📞
EMERGENCY ALARM/CALL
 Emergency Alarm can be sent to other radios via the one touch programmable button, establishing an emergency call in a specific group. Improves your emergency response time.
- 📶
PSUEDO TRUNK (Optional)
 This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency and allows you to communicate in a timely manner in emergency situations.
- RRS
RADIO REGISTRATION SERVICE
 RRS allows the PD485 to communicate with Smart Dispatch and SmartOne, so that the dispatcher can check if the radio is on or offline.
- 📄
SUPPLEMENTARY FEATURES (Optional)
 The PD485 can provide radio enable/disable, remote monitor and priority interrupt as optional features.
- 📍
ROAMING (Optional)
 Roam from each repeater site to have a non-stop voice transmission.
- 📶
GPS POSITIONING (Factory Optional)
 The built-in GPS module and GPS antenna are designed for outdoor positioning, making it the ideal tool to support location based requirements.
- 📶
BUILT-IN BLUETOOTH (Factory Optional)
 Built-in Bluetooth supports PD485 wireless audio accessories and other Bluetooth transmissions.
- 🛡️
RELIABLE AND DURABLE
 The PD485 is compliant with Mil-STD-810 G and IP54.
- 🎧
VOX
 This feature allows you to activate the radio microphone at speaking volume, so that you do not need to press the PTT.

Target Markets



FLEET MANAGEMENT

With RRS, the PD485 can be accessed by dispatch applications for effective radio fleet management. Whether it's voice dispatching, SDS messaging or location based services, the PD485 is ideal for team communications.



COMMERCIAL

Clear digital voice processors and powerful audio output ensures you receive your transmission even in noisy environments. Use the wireless earpiece or other audio accessories to improve your operating experience.



SECURITY

Privacy in any voice or data communication is essential for security teams. Emergency call, priority interrupt and remote monitor functions provide a reliable communication system to support security staff who always need to remain alert and connected.



OUTDOOR ADVENTURES

Flexible to program through the front panel and built to military standards, achieving IP54 rating for water and dust ingress protection, the PD485 is ready for your next adventure.

Standard



Li-ion Battery
(2000mAh)
BL2010



Belt Clip
BC19



General MCU Rapid-rate Charger
(for Li-Ion/Ni-MH Batteries)
CH10A07



Stubby Antenna



Switching Power Adapter



Hand Strap

Options



EHM19
C Style Earbop Earpiece
with On-MIC PTT



EAM12
Detachable Transparent
Acoustic Tube Earpiece
with PTT&MIC
cable



EAM13
2-wire Surveillance
Earpiece with VOX &
Transparent Acoustic
Tube (Black)



EHM20
Swivel Earpiece with
PTT&MIC cable



SM26M1
Remote Speaker
Microphone without
emergency button
(IP54)



ESM12
Earbud with On-MIC
PTT and VOX
switch



PC76
Data Programming
Cable



Antenna



MCA08



MCU Multi-unit Rapid
rate Charger

CH10A06



Dual Pocket MCU Charger Kit
(for Li-Ion/Ni-MH Batteries)
(charger + power s
upply cable)



LCY015
Nylon Carrying
Jacket

Specifications

General	
Frequency Range	UHF: 350-470MHz VHF: 136-174MHz
Channel Capacity	256
Zone Capacity	16
Channel Spacing	25/12.5KHz
Operating Voltage	7.4V
Battery	2000mAh (Li-Ion)
Battery Life (5/5/90)	Analogue /Digital: 12/16 hours
Weight	308g
Dimensions	117×55×37mm
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Receiver	
Sensitivity (Digital)	0.22μV / BER 5%
Sensitivity (Analog)	0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603 60dB @ 12.5KHz/70dB @ 25KHz
	ETSI 60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603 70dB @ 12.5/25KHz
	ETSI 70dB @ 12.5/25KHz
Inter-modulation	TIA-603 70dB @ 12.5/25KHz
	ETSI 65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @ 25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3

Environmental	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 G Standard
Shock & Vibration	Per MIL-STD-810 G Standard

PD48X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.
All specifications are subject to change without notice due to continuous development.

Your Hytera partner:



Hytera Communications Corporation Limited

Address: Hytera Communications (UK) Co. Ltd.
Hytera House, 939 Yeovil Road, Slough, Berkshire. SL1 4NH, UK.
Tel: +44 (0) 1753 826 120 **Fax:** +44 (0) 1753 826 121
www.hytera.co.uk info@hytera.co.uk

Further information can be found at:
www.hytera.co.uk

Keep up to date with Hytera on social media.



Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.

Encryption features are optional and have to be configured separately. They are also subject to European export regulations.

HYT Hytera are registered trademarks of Hytera Communications Corp. Ltd. © 2017 Hytera Communication Corp., Ltd. All rights reserved.